



Data Center Power Metering Pollable via RS232

Power Metering and Alarm Functions

- True RMS Current Metering per In-Feed & Branch Circuit
- Data Center Power Polling via RS232 RJ45 Port
- 3-Digit LED Digital Amp Load Display
- Branch Indicator LEDs
- 80% Threshold Alarms

Metered Outlets

- Network-grade Power Distribution for UL 60950-1 Branch Circuit Protection
- Multiple Branch Circuits per In-Feed
- 8/16/24 Outlets
- 20/30 Amp Single Phase 100/250V AC
- 20 & 30 Amp 208V 3-Phase
- Always On Outlets
- Detachable & Fixed Input Cords

Rack Mounting

- Zero U Vertical & 1U Horizontal Mounting
- Universal & Tool-less Mounting Brackets



Model BPM-24VS20-2

WTI's BPM Series PDUs provide system administrators with a convenient tool for distributing power to network equipment at the rack level, balancing current loads and preventing tripped circuit breakers!

BPM Series PDUs use true RMS current metering to display total amperage load per in-feed and on each branch circuit. An invertible LED display option allows you to read current load when the unit is mounted upside-down for overhead power delivery to the rack. Threshold alarms indicate 80% load capacity per in-feed or branch circuit.

The BPM is available in a variety of models and configurations to accommodate the power distribution needs of almost any application. Using UL 489 circuit breakers to comply with UL 60950-1 standards and quality manufacturing techniques, the BPM provides a metered PDU built and delivered with the high level of quality, service and support that the industry has learned to expect from WTI products.



Pollable via RS232



Model BPM-8HVS20-2



Model BPM-24VS20-1

Model BPM-16VS20-1



Model Number	Outlets	AC Voltage 50/60 Hz	Power Distribution (80% Derated)	Input Feed	Power Cord (Sold Separately) Lengths and Styles Vary	Dimensions L"xW"xD"
--------------	---------	------------------------	-------------------------------------	------------	--	------------------------

Horizontal/Vertical Mounting

BPM-8HS20-1	(8) NEMA 5-20R	85 - 125V	1.4 - 2 kW	20 Amp	Detachable	17x1.75x3.31
BPM-8HS20-2	(8) IEC 60320 C13	200 - 250V	3.2 - 4 kW	20 Amp	Detachable	17x1.75x3.31

Vertical Mounting

BPM-16VS20-1	(16) NEMA 5-20R	85 - 125V	1.4 - 2 kW	20 Amp	Detachable	32x1.95x3.1*
BPM-16VS20-2	(16) IEC 60320 C13	200 - 250V	3.2 - 4 kW	20 Amp	Detachable	32x1.95x3.1*
BPM-16VS30-1	(16) NEMA 5-20R	85 - 125V	2 - 3 kW	30 Amp	Fixed - NEMA L5-30P	32x1.95x3.1*
BPM-16VS30-2	(16) IEC 60320 C13	200 - 250V	4.8 - 6 kW	30 Amp	Fixed - NEMA L6-30P	32x1.95x3.1*
BPM-24VS20-1	(24) NEMA 5-20R	85 - 125V	1.4 - 2 kW	20 Amp	Detachable	52x1.95x3.1*
BPM-24VS20-2	(24) IEC 60320 C13	200 - 250V	3.2 - 4 kW	20 Amp	Detachable	52x1.95x3.1*
BPM-24VS30-1	(24) NEMA 5-20R	85 - 125V	2 - 3 kW	30 Amp	Fixed - NEMA L5-30P	52x1.95x3.1*
BPM-24VS30-2	(24) IEC 60320 C13	200 - 250V	4.8 - 6 kW	30 Amp	Fixed - NEMA L6-30P	52x1.95x3.1*

Vertical Mounting 3-Phase

BPM-24VS20-D	(24) IEC 60320 C13	208V 3Ø	5.7 kW	20 Amp	Fixed - NEMA L15-20P	52x1.95x3.1*
BPM-24VS20-Y	(24) IEC 60320 C13	208V 3Ø	5.7 kW	20 Amp	Fixed - NEMA L21-20P	52x1.95x3.1*
BPM-24VS30-D	(24) IEC 60320 C13	208V 3Ø	8.6 kW	30 Amp	Fixed - NEMA L15-30P	52x1.95x3.1*
BPM-24VS30-Y	(24) IEC 60320 C13	208V 3Ø	8.6 kW	30 Amp	Fixed - NEMA L21-30P	52x1.95x3.1*

* 3.1" maximum depth

Model BPM-24VS30-1



- ✓ 5 Year Warranty
- ✓ Stocked for Same Day Shipments
- ✓ In-House Design & Manufacturing
- ✓ Made In USA

For More Information:

Call: **(800) 854-7226** **Or Visit:** **www.wti.com**

Metered Rack Mount PDUs