



# Remote Power Reboot Switches

## NBB Series

### Control Power to AC Powered Devices via Browser, Telnet, Modem or Terminal

#### Power Control & Management:

- Remote Power Management and Control
- Reboot Servers, Routers, Switches, Web Cams, Firewalls and Other Remote Devices
- Sixteen (16) Individual Switched Outlets
- On/Off/Reboot/Default Switching
- User-Defined Power-Up Default Status
- User-Defined Sequence Delay Times
- Ideal for Lab, Test & Academic Applications
- Manual Power Control Button
- 120 & 240 VAC Models Available
- 10, 15, 16 & 20 Amp Models Available

#### Accessibility:

- In-Band: 10/100Base-T Ethernet Port
- Out-of-Band: External Modem Ready
- Local: DB9 RS232 Set Up Port

#### Security:

- Encrypted Passwords
- IP Address Filtering
- Plug Specific Passwords
- Two Separate Password Access Levels

#### Unit Management:

- Command Line Interface (CLI) Plus Web-Based Graphic User Interface (GUI)
- Automated Mode Allows Code-Driven Power Control by Another Device
- Zero-U Rack Mountable



Model NBB-1600

Servers, routers, and other electronic equipment sometimes “lock-up,” often requiring a service call to a remote site just to flip the power switch to perform a simple reboot. The NBB Internet Power Switch gives you the ability to reboot rack mount equipment remotely; point your browser to the NBB’s TCP/IP address, enter the secure user name and password, and you’re just a click away from remote power On, Off or Reboot!

The NBB provides two convenient interfaces for accessing configuration and control functions; a Web Browser Interface and a Command Line Interface.

The Web Browser Interface consists of a series of easy-to-use web page menus that allow you to select parameters or initiate switching operations using your TCP/IP network and a JavaScript enabled web browser. The Command Line Interface is an ASCII menu system which allows you to configure and operate the IPS via telnet over TCP/IP network, via external modem connection or via local PC using any common terminal program.



# Remote Power Reboot Switches

## NBB Series

| Model Number   | Outlets           | AC Voltage 50/60 Hz | Power Distribution (80% Derated) | Input Feeds | Power Supply Cord               | Dimensions                                                     |
|----------------|-------------------|---------------------|----------------------------------|-------------|---------------------------------|----------------------------------------------------------------|
| NBB-1600       | (16) NEMA 5-15    | 85/125V             | 2 - 3 kW                         | (2) 15 Amp  | 2 ea., NEMA 5-15P, 6'           | L: 43.75" (111.1 cm)<br>D: 3.00" (7.6 cm)<br>W: 1.75" (4.5 cm) |
| NBB-1600-CE    | (16) IEC60320-C13 | 200/250V            | 3.2 - 4 kW                       | (2) 10 Amp  | Detachable<br>(Sold Separately) |                                                                |
| NBB-1600-D20   | (16) NEMA 5-15    | 85/125V             | 2.7 - 4 kW                       | (2) 20 Amp  |                                 |                                                                |
| NBB-1600CE-D16 | (16) IEC60320-C13 | 200/250V            | 5.1 - 6.4 kW                     | (2) 16 Amp  |                                 |                                                                |
| NBB-1600E-D20  | (16) IEC60320-C13 | 200/250V            | 6.4 - 8 kW                       | (2) 20 Amp  |                                 |                                                                |

|                               |                           |
|-------------------------------|---------------------------|
| <b>Ethernet Port:</b>         | 10 BaseT, RJ45            |
| <b>Console Port:</b>          | DB9M, RS232C              |
| <b>Operating Temperature:</b> | 32°F - 122°F (0°C - 50°C) |
| <b>Humidity:</b>              | 10 - 90% RH               |
| <b>Shipping Weight:</b>       | 12 Lbs (5.4 Kg)           |
| <b>Mounting:</b>              | Zero-U Mounting           |
| <b>Approvals:</b>             | UL, cUL, CE, FCC Class A  |

Model NBB-1600-CE



**For More Information:**  
**Call:** (800) 854-7226  
**Or Visit:** [www.wti.com](http://www.wti.com)

- ✓ 5 Year Warranty
- ✓ Stocked for Same Day Shipments
- ✓ In-House Design & Manufacturing
- ✓ Made In USA

# Remote Power Reboot Switches